

UVPV Module

STAND-ALONE MODULE FOR DIRECT DRIVING OF HYDRAULIC VALVES WITH SOLENOID CURRENT CONTROL

UVPV is a stand-alone module for direct driving of hydraulic valves with solenoid current control.

The space required for installation is minimized by the vertical design of the module.

The module can drive 1 or 2 solenoids, depending on the type of valve: pressure or flow rate. Two different modules are available depending on the feedback signal source being internal or external.

In case of internal feedback the reference signal is a current signal that must be taken from the first analog input, and the feedback loop closes on the output current measured inside the module.

In case of external feedback the reference signal that must be taken from the first analog input is of varying typology, and it must have the same physical dimensions of the feedback signal, measured on the second analog input. The feedback loop typology can be:

- pressure loop with external pressure transducer;
- flow rate loop if an external flow rate transducer is available;
- position loop of an hydraulic cylinder using an external analogic position transducer mounted on a stand.

Calibration, and parameterization are performed via the USB port available on the module. It is possible to calibrate loop parameters, and the following additional settings are available:

- 5 point input characteristic linearization with deadband, and threshold handling.
- Ramp to set the time to bring the reference from 0 to maximum.
- Dither to be overlayed to the output current signal and whose frequency, and amplitude can be set.

Analog inputs can be connected from differential voltage inputs with dynamics 0/10 V or +10/-10 V, current signals with dynamics 4/20 mA, and potentiometric transducers powered by the module.

4 groups of spring-cage connectors are provided:

- One 4 points group, of which only 2 are used for 24 V power supply, and the other 2 are unused;
- Two 4 points group with the following purpose:
 - Potentiometer power supply positive pole;
 - Differential voltage signal input negative pole / Current input negative pole;
 - Differential voltage signal input positive pole / Current input positive pole / Potentiometric cursor;
 - Potentiometer power supply negative pole;
- One 4 points connector, two for the positive solenoid, and two for the negative solenoid;
- One Type B miniUSB connector.



Technical specifications

Dimensions (H x W x D)	120 x 22,5 x 114 mm
Mounting	Standard DIN rail
Power supply	24 V (18 – 36 V)
Module logic power consumption	100 mA
Analog input channels	2
Differential input voltage	0/10 V o -10/10 V
Input current	4/20 mA
Minimum potentiometer resistance	1 KOhm
Potentiometer voltage reference	10 V
ADC converter resolution	12 bit
Power outputs	1, for a bi solenoid valve
Nominal power output current	2,5 A
Power output protection	Shortcircuit
Set-point linearization	Up to 5 points
PWM frequency	1 kHz
Dither frequency	From 50Hz to 150 Hz
Dither amplitude	Up to 50%
Marking	CE
Operating Temperature	0 ÷ 55°C
Warehousing Temperature	-20 ÷ 85 °C
Storage Humidity	Max 95% non-condensing